

Tower 2.0



Tower 2.0 7-Port USB 2.0 HUB

Up to 7 peripheral USB 2.0 devices such as mice, numeric keyboards, CD burners, card readers or scanners can simultaneously be connected to and powered by the new HUB Tower 2.0 from DICOTA. Tower 2.0 is reverse compatible with the USB standard 1.1.

The USB 2.0 devices are detected instantly via Plug & Play, which spares an extensive or complicated installation. Tower 2.0 is especially customized for the requirements of Notebook users. The data transfer rate lies at 480 Mbps and is 40 times higher than that of the USB standard 1.1.

7-Port USB 2.0 HUB (reverse compatible with USB 1.1) . data transfer rate of up to 480 Mbps (1.5/12/480 Mbps). Plug & Play & Hot Swapping, Over-current detection and protection. USB 2.0 cable. external power supply. user's guide

Art. Nr.: Z13388Z ()
Material: Plastic/Metal
Weight: 0.15 kg / 0.33 lbs
Dimensions: 90 x 65 x 25 mm / 3.5 x 2.6 x 1 inch



DICOTA BeNeLux
Jean-Claude Buysens
Luitenant Lippenslaan 48
2140 Borgerhout

Phone: +32 3 66 33 515
FAX: +32 32 71 29 81

dicota@skynet.be